



**MAXAM**  
NORTH AMERICA

# MS708

**OTR PRO**

Applications:



Engineered for wheeled loaders operating in the most severe waste, recycling, and mining applications.

- Low durometer center compound, combined with patented "Double D" apertures provide excellent ride vs 2-stage products
- True 3-stage all rubber design for reduced heat generation and high cut resistance
- Zero maintenance and downtime for maximum productivity
- Available in smooth or traction tread designs for maximum versatility in all applications
- Mounts on standard multi-piece earthmover rims

Size	Tread	Sidewall	Rim	O.D.	S.W.	T.D.	L.C.C (lbs)		L.I.
				in	in	in	5 mph	10 mph	
17.5-25	SM	ST	14.00	53.0	17.8	6.1	24700	17890	192A2
	SM	AP	14.00	53.0	17.8	6.1	22230	16100	188A2
	TR	ST	14.00	53.0	17.8	6.1	24700	17890	192A2
	TR	AP	14.00	53.0	17.8	6.1	22230	16100	188A2
20.5-25	SM	ST	17.00	58.8	20.8	7.4	35300	25570	204A2
	SM	AP	17.00	58.8	20.8	7.4	30900	22380	200A2
	TR	ST	17.00	58.8	20.8	7.4	35300	25570	204A2
	TR	AP	17.00	58.8	20.8	7.4	30900	22380	200A2
23.5-25	SM	ST	19.50	64.0	23.5	8.6	44100	31950	212A2
	SM	AP	19.50	64.0	23.5	8.6	39700	28760	208A2
	TR	ST	19.50	64.0	23.5	8.6	44100	31950	212A2
	TR	AP	19.50	64.0	23.5	8.6	39700	28760	208A2
26.5-25	SM	ST	22.00	68.4	27.0	9.5	53600	38830	219A2
	SM	AP	22.00	68.4	27.0	9.5	48100	34840	215A2
	TR	ST	22.00	68.4	27.0	9.5	53600	38830	219A2
	TR	AP	22.00	68.4	27.0	9.5	48100	34840	215A2
29.5-25	SM	ST	25.00	73.0	29.7	10.4	66000	47810	226A2
	SM	AP	25.00	73.0	29.7	10.4	58400	42305	222A2
	TR	ST	25.00	73.0	29.7	10.4	66000	47810	226A2
	TR	AP	25.00	73.0	29.7	10.4	58400	42305	222A2

